

Catalog Number: EX06MLC2K
Product ID: 7TCA297180R0398
UPC Number: 78621019824
EAN Number: 05011949235151
Status: Active

Single Compression Cable Gland, M32 Thread, For Use with Non-Armoured Cable, Flame-proof Ex d and Increased Safety Ex e, IP66-68 Rating, Length 53mm, Cable Range 22 to 26mm, Kit with Locknut, Shroud, Earth Tag, and Washer, Brass

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Kopex
Type	Single Compression Cable Gland
Special Features	Kit Comes with Locknut, Shroud, Earth Tag, and Washer
Application	For Use with Unarmoured Cable to Provide Secure Cable Connections Through Knockouts and Threaded Entries
Standard	UL Listed, Approved to EN60079-0, 60079-1, 60079-7, 60079-31
Size	M32
Conductor Range	22 to 26 Millimeters
Material	Brass
Color	Metallic
Insulation	IP66-68 Rating
Temperature Rating	-40 to 80 Degrees C
Environmental Conditions	Flameproof Ex d and Increased Safety Ex e

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	Metric
Nominal thread size metric/PG	32
Pitch thread	1.5mm
Thread length	16mm
Hexagon angular dimension	49.5mm
Suitable for cable diameter	22.0-26.0mm
Material	Metal
Material quality	Brass
Surface protection	Untreated
Halogen free	N
Glass-fibre reinforced	N
Degree of protection (IP)	IP68
Shock resistant	N
Colour	Natural colour
Bend radius protection/trumpet flare	N
With locknut	Y
Model	Straight
Flat cable coupling	N
Strain relief	N
Operating temperature	-40-+80°C
Explosion-tested version	Y
For Ex-zone gas	None
For Ex-Zone dust	None
EMC-version	N

Packaging

Inner Quantity	1
Inner Dimensions (inches)	.39x5.71x5.91
Outer Quantity	30
Outer Dimensions (inches)	7.87x15.75x11.02
Weight Uom	1.28 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com