UTRS220A

Individual meter socket, ringless socket, no bypass, 4 jaws no release, UG, 200 A, up to 600 VAC single phase 3W



Main	
Product or Component Type	Meter Socket
Meter socket type	Ringless
Hub type	Solid top

Complementary

Complementary	
Meter socket rated current	200 A
Number of jaws	4 without jaw release
Bypass type	No bypass
Phase	1 phase
[Ue] rated operational voltage	600 V AC
Enclosure Material	Steel
Electrical connection	Studs 0.375" hex
Service feed location	UG
Wiring configuration	3-wire
Device mounting	Surface

Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901367635
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.10 in (15.494 cm)	
Package 1 Width	13.80 in (35.052 cm)	
Package 1 Length	15.60 in (39.624 cm)	
Package 1 Weight	14.64 lb(US) (6.641 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
Contractual warranty	
Warranty	18 months