

Catalog Number: T8VBE3HR0AADAAX
UPC Number: 80432555874
Status: Active

TMAX Breaker frame size T8, 2500A, 3 pole, long time, short time and instantaneous protection functions, very high 125kA @ 480V breaking capacity, 24 VDC closing coil, 4 auxiliary contacts (supplied as standard for breakers with PR332 trip units), 220-250 VAC/DC spring charging motor, 24 VDC shunt trip, 24 VDC undervoltage - second shunt trip, mechanical counter and bell alarm with remote reset 220-240 VAC/DC, Underwriters Laboratories (sold in the US)

North American Specifications (UNSPSC)

UNSPSC	39121616 Molded case circuit breakers
IGCC	4927 Molded case circuit breakers
Brand Name	ABB
Sub Brand	Tmax
Type	Molded case circuit breaker
Standard	UL 489, CSA, IEC 60947-2
Current Rating	2500 (3P)
Trip Type	PR332/P-LSI
Interrupt Rating	Very High
Auxiliary Contacts	4 aux contacts; (supplied as standard for breakers with PR332 trip units)

Packaging

Outer Quantity	1
Outer Dimensions (inches)	27.362x20.669x18.701
Weight Uom	34.79 lbs. Each

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com