Miller Contractor Harness

Models: 650CN Series

Description

The Miller Contractor Harness is specifically designed for use in construction with the unique combination back D-ring pad/shoulder pads that minimize discomfort/stress around the neck and shoulders when using a tool belt. All harnesses come equipped with a back D-ring and sub-pelvic strap.

Materials

Webbing: 1 ¾" Polyester

Elastic Keepers: Polyester, Nylon, Lycra

Thread: 6 cord bonded 3 strand polyester

thread. Minimum tensile of 42 lbs

D-ring: Clear Chromate Finished Carbon

Steel

Hardware: Steel
Grommets: Brass
Labels: Valeron

Label Pack: Evoprene, Nylon

*All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max. Working Load:400 lbs (181kg)Webbing Min.Tensile:5,000 lbs (22kN)D-ring Min. Tensile:5,000 lbs (22kN)Buckle Min. Tensile:4,000 lbs (18kN)

Certification

Meets OSHA 1910.66, 1926.502 (d), ANSI A10.32, Z359-2007 and CSA Z259.10-06 specifications.



| SKU | Side D-Rings | Chest Strap | Shoulder Strap | Leg Straps | Weight | Special Features |
|---------------|-----------------|----------------|-------------------|---------------|--------------------|--|
| 650CN-BP/UGN | No | Mating | Friction | Tongue | 4.42 lbs (2kg) | D-ring pad / Shoulder pads / Pull-free lanyard rings / Belt loops / 4 ½" Belt Pad |
| 650CN-BDP/UGN | Yes | Mating | Friction | Tongue | 5.2 lbs (2.3kg) | D-ring pad / Shoulder pads / Side D-rings / Pull-free lanyard rings / Belt loops / 4 1/2" Belt Pad |

Note: For front D-ring vest-style option, add "FD" to the corresponding harness model number (Ex. 650CNFD-BP/UGN). Model numbers listed are for universal size. Harnesses are also available in small/medium and XXlarge, by replacing the "U" in the model number with "S/M" or "XXL" (Ex. 650CN-BP/XXLGN or 650CN-BP/S/MGN).



by Honeywell

Toll Free 800.873.5242 (press 4) • hsptechsupport@honeywell.com • www.millerfallprotection.com

WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.