

Catalog Number: UPC Number: Status:

TS3L100TW 80432534945 Active

Circuit Breaker TMAX Ts3L 150 UL/CSA FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 100-1000 A

North American Specifications (UNSPSC)

(UNOFOC)
39121616 Molded case circuit breakers
4927 Molded case circuit breakers
ABB
Tmax
Molded case circuit breaker
Features: The Ts3 Breaker Family Ranges From
15 Through 225 AMP; The Ts3 Trip Mechanisms
Are Non-Interchangeable And Use Sensitive Elec-
tromagnetic Relays For Overcurrent Trip Protec-
tion; Heat Sensitive Bimetals Are Used For Thermal
Overcurrent Protection; Short Circuit Current Pro-
tection Begins At 10 Times The Thermal Rating Of
The Breaker And Uses A Magnetic Coil Principle;
Interrupting Rating Class/breaking Capacity: Extra
High; Mechanical Life: 25000 Operations; Weight:
6.750 LB; Ts3I100tw: BKR TS3L 100A 3P T/M UL
LVP
UL 489, CSA, IEC 60947-2
100A
225A
Thermal-magnetic
Extra High
Nama
None

Pa	СКа	agi	ng

Outer Quantity	1
Outer Dimensions (inches)	7.6x1x9.3
Weight Uom	6.45 lbs. Each

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120

Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com